

# OMNI-VS

## VITAL SIGNS MONITOR



### Non-Invasive Blood Pressure, SpO<sub>2</sub>, Stat-Temperature

- Suitable for adult, pediatric and neonatal patients
- Nellcor SpO<sub>2</sub> technology
- SureTemp™ thermometer provides an accurate reading within seconds
- Adjustable audible and visual alarms
- Removable and rechargeable battery, up to 6-hour working time
- Integrated handle and full mounting solutions
- Motion Tolerant NIPB and SPO<sub>2</sub>
- Integrated printer



Advanced, Affordable Medical Technology For The World

# OMNI-VS VITAL SIGNS MONITOR TECHNICAL SPECIFICATIONS

## Safety

Meet the requirements of IEC60601 series, CE marking according to MDD93/42/EEC

## Dimension and Weight

Dimension: 170mm (W) x 240mm (H) x 170mm (D)  
Weight: < 3.5kg (including a battery)

## Operation Environment

AC Power Requirements: 100-240VAC ( $\pm 10\%$ ), 50/60 Hz ( $\pm 3$  Hz), 70VA  
Temperature: 0-40°C (SureTemp™: 10-40°C)  
Humidity: 15%-95%, non-condensing

## Patient Range

Adult, pediatric and neonatal

## NIBP

Method: Automatic oscillometric  
Operation modes: Manual / Automatic / Continual  
Auto measure time: Adjustable  
Measurement unit: mmHg / kPa selectable  
Measurement types: Systolic, Diastolic, Mean, Pulse Rate  
Measurement range: Adult: 10-270mmHg  
Pediatric: 10-200mmHg  
Neonate: 10-135mmHg

## Over-pressure

protection: YES  
Resolution: 1mmHg  
Alarm: Systolic, Diastolic, Mean, Pulse Rate  
Pulse Rate Range: 40-240 bpm  
Pulse Rate Resolution: 1bpm  
Pulse Rate Accuracy:  $\pm 2$ bpm

## SpO<sub>2</sub>

Measurement range: 0-100%  
Resolution: 1%  
Accuracy: Adult/Pediatric:  $\pm 2\%$  (70-100%);  
Neonatal:  $\pm 3\%$  (70-100%);  
0-69% unspecified  
Alarm range: 0-100%  
Pulse rate: Range: 20-254bpm  
Resolution: 1bpm  
Accuracy:  $\pm 3$ bpm  
Alarm range: 20-254bpm

## Nellcor OxiMax SpO<sub>2</sub>

Measurement range: 0-100%  
Compatible sensors: Nellcor sensor type: OxiMax series MAX-A, MAX-AL, MAX-N, MAX-P, MAX-I, MAX-FAST, MAX-R, OxiCliq A, OxiCliq N, OxiCliq P, OxiCliq I, D-YS, D-YSE, D-YSPD, DS-100A, OXI-AIN and OXI-P/I  
SpO<sub>2</sub> accuracy: 70%-100%  $\pm 2\%$ ; 0-69% unspecified (sensors: MAX-A, MAX-AL, MAX-N, MAX-P, MAX-I and MAX-FAST)  
70%-100%  $\pm 2.S\%$ ; 0-69% unspecified (sensors: OxiCliq A, OxiCliq N, OxiCliq P and OxiCliq I)  
70%-100%  $\pm 3\%$ ; 0-69% unspecified (sensors: D-YS, DS-100A, OXI-A/N and OXI-P/I)  
70%-100%  $\pm 3.5\%$ ; 0-69% unspecified

## Pulse Rate

Range and accuracy: 20-250 bpm  $\pm 3$  bpm  
251-300 bpm unspecified

## SureTemp™ Thermometer

Measurement range: 25 - 44°C (77-111.2 °F)  
Resolution: In MONITOR mode: 0.1°C (0.2 °F)  
Accuracy: In MONITOR mode: 25-32°C (77-89.6 °F) :  $\pm 0.2^\circ\text{C}$  ( $\pm 0.3^\circ\text{F}$ ) including 32°C (89.6 °F)  
In MONITOR mode: 32-44°C (89.6-111.2 °F) :  $\pm 0.1^\circ\text{C}$  ( $\pm 0.2^\circ\text{F}$ ) excluding 32°C (89.6 °F)

Typical Measurement time: < 12s



Rolling Stand with Basket Available

Authorized Distributor:



12151 62nd St N #5 • Largo FL 33773 • USA  
Phone: (1) 727-531-8434 • Fax: (1) 727-531-8436  
Web: [www.infiniummedical.com](http://www.infiniummedical.com) • Email: [sales@infiniummedical.com](mailto:sales@infiniummedical.com)